CORPORATE HEADQUARTERS
P.O. BOX 2069, BELLINGHAM, WA, U.S.A.
TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0679 Stroke/Edge Sander

Converts to an Edge Sander...

MACHINE HIGHLIGHTS (*see Machine Data Sheet for full specifications*)

- 3 HP, 220V, single-phase motor with built-in brake that quickly stops belt movement.
- Head position swivels horizontal for stroke sanding or vertical for edge sanding!
- Stroke sands workpieces up to 59" wide by 21" thick.
- Edge sander platen is 69" long and table, in edge-sander mode, easily holds full-sized doors.
- Sliding table travels on ball bearings for ultra-smooth workpiece positioning.
- Graphite-coated platen moves to both sides of the table and features a 1¼" down stroke.

The Model G0679 Stroke/Edge Sander is available for $2,995.00. As with all Grizzly products, the Model G0679 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit **www.grizzly.com**.

MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0679 6" X 186" 3 HP 220V STROKE SANDER

Product Dimensions:

Weight	608 lbs.
Length/Width/Height	98 x 47-5/8 x 67-1/2 in.
Foot Print (Length/Width)	69-1/4 x 31 in.

Shipping Dimensions:

Type	Wood Crate
Content	Machine
Weight	744 lbs.
Length/Width/Height	87 x 37 x 24 in.

Electrical:

Minimum Circuit Size	30A
Switch	Magnetic with Thermal Overload Protection
Switch Voltage	220V
Cord Length	6 ft.
Cord Gauge	14 gauge
Plug Included	No
Recommended Plug/Outlet Type	L6-30

Motors:

Main

Type	TEFC Capacitor Start Induction
Horsepower	3 HP
Voltage	220V
Phase	Single
Amps	17A
Speed	1750 RPM
Cycle	60 Hz
Number Of Speeds	1
Power Transfer	Direct Drive
Bearings	Shielded and Permanently Lubricated

Main Specifications:

Operation Information

Sanding Belt Speed	3600 FPM
Sanding Belt Length	186 in.
Sanding Belt Width	6 in.

Table Information

Table Length	23-3/4 in.
Table Width	59 in.
Table Thickness	3 in.
Table Travel	18 in.
Floor To Table Height	21-3/8 - 42-3/4 in.

The information contained herein is deemed accurate as of 5/7/2010 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.

Platen Information

Platen Type..... Graphite/Rubber
Platen Length..... 10-1/2 in.
Platen Width..... 6 in.
Platen Travel..... 50-1/2 in.

Construction

Table Construction..... Steel Tube Foundation with Particle Board Work Surface
Frame Construction..... Steel Tube
Base Construction..... Steel Tube
Drive Roller Construction..... Aluminum
Paint..... Powder Coated

Other Related Information

No Of Dust Ports..... 2
Dust Port Size..... 4 in.

Other Specifications:

ISO Factory ..... ISO 9001
Country Of Origin ..... Taiwan
Warranty ..... 1 Year
Serial Number Location ..... ID Label on Front of Machine
Assembly Time ..... 3 Hours

Features:

21 In. Maximum Workpiece Thickness
Horizontal Belt Position for Stroke Sanding and Vertical Belt Position for Edge Sanding
Sliding Ways Travel on Ball Bearings
Fully Adjustable Belt Tracking and Tension
Motor Brake Quickly Stops Belt Movement

The information contained herein is deemed accurate as of 5/7/2010 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.