



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0529 OSCILLATING SPINDLE / 12" DISC SANDER

Product Dimensions:

Weight..... 166 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 32 x 18 x 47 in.
Footprint (Length x Width)..... 21-1/4 x 16-1/2 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 181 lbs.
Length x Width x Height..... 34 x 30 x 21 in.

Electrical:

Minimum Circuit Size..... 15 amp
Switch..... ON/OFF Toggle with Safety Key
Switch Voltage..... 110V
Cord Length..... 6 ft.
Cord Gauge..... 14 gauge
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1 HP
Voltage..... 110V
Prewired..... 110V
Phase..... Single
Amps..... 10A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Direct/Gear Drive
Bearings..... Sealed and Permanently Lubricated

Main Specifications:

Table Info

Table Width..... 14-1/2 in.
Table Length..... 14-1/2 in.
Table Thickness..... 1 in.
Table Tilt..... 0 - 45 deg.
Table Opening..... 5 in.
Table Inserts..... 1-1/8, 1-1/8, 2, 2-1 in.
Floor To Table Height..... 42 in.
Miter Gauge Slot Width..... 3/4 in.
Miter Gauge Slot Height..... 3/8 in.
Disc Table Length..... 17-3/4 in.
Disc Table Width..... 10 in.
Disc Table Thickness..... 1 in.

Spindle Info

Spindle Diameter..... 1/4, 5/8, 1-1/2, 2 in.
Spindle Lengths..... 5-1/2 in.
Spindle Speed..... 1725 RPM
Spindle Oscillation..... 60 SPM
Stroke Length..... 1 in.

Disc Info

Sanding Disc Diameter..... 12 in.
Sanding Disc Speed..... 1725 RPM

Construction

Base..... Preformed Steel
Stand..... Preformed Steel
Table..... Precision Ground Cast Iron
Frame..... Cast Iron
Disc..... Computer Balanced Aluminum
Miter Gauge..... Plastic with Steel Bar
Paint..... Powder Coated

Other

No. Of Dust Ports..... 2
Dust Port Size..... 2 in.
Mobile Base..... G7314Z

Other Specifications:

ISO Factory ISO 9001
Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location Front of Stand
Assembly Time 45 minutes

Features:

- Four Spindle Sizes
- Miter Gauge Included
- Includes Formed and Welded Steel Stand
- Both Tables Tilt
- Two Cast Iron Tables
- Safety Paddle Switch with Lock