



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0606X1 12" 7-1/2 HP 3-PHASE EXTREME TABLE SAW

Product Dimensions:

Weight..... 715 lbs.
 Width (side-to-side) x Depth (front-to-back) x Height..... 91-1/2 x 79-1/2 x 42-1/2 in.
 Footprint (Length x Width)..... 22-1/2 x 24 in.
 Space Required for Full Range of Movement (Width x Depth)..... 91-1/2 x 79-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Wood Crate
 Content..... Machine & Extension Tables
 Weight..... 783 lbs.
 Length x Width x Height..... 46 x 43 x 42 in.
 Must Ship Upright..... Yes

Carton #2

Type..... Wood Crate
 Content..... Front & Rear Rails
 Weight..... 88 lbs.
 Length x Width x Height..... 97 x 8 x 9 in.
 Must Ship Upright..... No

Carton #3

Type..... Cardboard Box
 Content..... Fence
 Weight..... 24 lbs.
 Length x Width x Height..... 45 x 19 x 9 in.
 Must Ship Upright..... No

Electrical:

Power Requirement..... 220V or 440V, 3-Phase, 60 Hz
 Prewired Voltage..... 220V
 Full-Load Current Rating..... 19.5A at 220V, 10A at 440V
 Minimum Circuit Size..... 30A at 220V, 15A at 440V
 Connection Type..... Cord at 220V, Hardwire at 440V
 Power Cord Included..... Yes
 Power Cord Length..... 10 ft.
 Power Cord Gauge..... 12 AWG
 Plug Included..... No
 Recommended Plug Type..... L15-30 for 220V
 Switch Type..... ON/OFF Push Button Switch w/Large Shut-Off Paddle & Padlock

Motors:

Main

Horsepower.....	7.5 HP
Phase.....	3-Phase
Amps.....	19.5A/10A
Speed.....	3450 RPM
Type.....	TEFC Induction
Power Transfer	Poly-V Belt Drive
Bearings.....	Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type.....	N/A

Main Specifications:

Main Information

Table Saw Type.....	Cabinet
Maximum Standard Blade Diameter.....	12 in.
Arbor Size.....	1 in.
Arbor Speed.....	3600 RPM
Maximum Width of Dado.....	3/4 in.
Blade Tilt Direction.....	Left
Max Blade Tilt.....	45 deg.
Maximum Depth of Cut At 90 Degrees.....	4 in.
Maximum Depth of Cut At 45 Degrees.....	2-3/4 in.
Max Rip Right of Blade w/Included Fence & Rails.....	52 in.
Max Rip Left of Blade w/Included Fence & Rails.....	18 in.

Additional Blade Information

Included Blade Information.....	12" x 60T
Riving Knife/Spreader Thickness.....	0.090 in.
Required Blade Body Thickness.....	0.074 – 0.082 in.
Required Blade Kerf Thickness.....	0.114 – 0.122 in.
Rim Speed at Max Blade Diameter.....	11,300 FPM

Table Information

Floor to Table Height.....	35-3/4 in.
Table Size with Extension Wings Width.....	78-3/4 in.
Table Size with Extension Wings Depth.....	69-1/2 in.
Distance Front of Table to Center of Blade.....	17-1/4 in.
Distance Front of Table to Blade At Maximum Cut.....	11-1/2 in.
Main Table Size Thickness.....	1-15/16 in.

Fence Information

Fence Type.....	Camlock T-Shape w/Aluminum Face
Fence Size Length.....	45-7/8 in.
Fence Size Width.....	15-7/8 in.
Fence Size Height.....	5 in.
Fence Rail Type.....	Square Steel Tubing/Angle Iron
Fence Rail Length.....	91-1/2 in.
Fence Rail Width.....	3 in.
Fence Rail Height.....	2 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

Construction

Table.....	Precision-Ground Cast Iron
Wings.....	Precision-Ground Cast Iron
Cabinet.....	Pre-Formed Steel
Trunnions.....	Cast Iron
Fence Assembly.....	Aluminum Extruded Body
Rails.....	Steel
Miter Gauge Construction.....	Aluminum Body with Steel Bar
Guard.....	Steel and Clear Plastic
Body/Cabinet Paint Type/Finish.....	Powder Coated
Arbor Bearings.....	Sealed & Permanently Lubricated

Other Related Information

Number of Dust Ports.....	1
Dust Port Size.....	4 in.

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	1 Hour
Serial Number Location	ID Label on Cabinet
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features:

- Quick-Release Blade Guard and Spreader
- Riving Knife Included
- Hinged Motor Cover
- 4" Dust Port
- Comfortable Polished Chrome Handles
- Heavy-Duty Miter Gauge
- Smooth and Quiet Poly-V Serpentine Belt System
- Precision-Ground Cast-Iron Table
- Outfeed and Extension Tables w/Storage Shelves
- Blade Angle Digital Readout
- Large Rail-Mounted Switch
- Heavy-Duty Legs
- Included 12 x 60T Carbide-Tipped Blade