



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

## MODEL G0675 JOINTER/PLANER COMBINATION MACHINE

### Product Dimensions:

Weight .....317 lbs.  
 Length/Width/Height .....46" x 27" x 38"  
 Foot Print (Length/Width).....26" x 22"

### Shipping Dimensions:

#### Carton #1

Type ..... Wood Crate  
 Content..... Machine  
 Weight.....348 lbs.  
 Length/Width/Height..... 44" x 25" x 25"

#### Carton #2

Type ..... Cardboard  
 Content..... Base  
 Weight.....30 lbs.  
 Length/Width/Height..... 29" x 14" x 7"

### Electrical:

Switch..... On/Off Buttons  
 Switch Voltage .....220V  
 Recommended Cord Gauge..... 14 Gauge  
 Recommended Breaker Size..... 15A  
 Plug.....NEMA 6-15

### Motors:

#### Main

Type ..... TEFC Capacitor Start Induction  
 Horsepower..... 2.5 HP  
 Voltage.....220V  
 Phase..... Single  
 Amps.....9.9A  
 Speed..... 3400 RPM  
 Cycle .....60 Hz  
 Number Of Speeds ..... 1  
 Power Transfer ..... Poly V-Belt  
 Bearings..... Shielded and Lubricated

### Main Specifications:

#### Fence Information

Fence Length.....35<sup>7</sup>/<sub>16</sub>"  
 Fence Height.....5<sup>7</sup>/<sub>8</sub>"  
 Fence Stops..... 45 and 90 deg.

#### Cutting Capacities (Jointer)

Bevel Jointing ..... 0-45 deg.  
 Maximum Width of Cut ..... 10<sup>1</sup>/<sub>4</sub>"  
 Maximum Depth of Cut.....<sup>1</sup>/<sub>8</sub>"  
 Number of Cuts Per Minute ..... 13000

**Cutting Capacities (Planer)**

Maximum Width of Cut .....	9 <sup>3</sup> / <sub>4</sub> "
Maximum Depth of Cut Planing Full Width.....	<sup>3</sup> / <sub>16</sub> "
Number of Cuts Per Minute .....	13000
Number of Feed Speeds.....	1
Feed Speed .....	16 FPM
Minimum Stock Length .....	11 <sup>13</sup> / <sub>16</sub> "
Maximum Stock Thickness .....	8 <sup>1</sup> / <sub>4</sub> "

**Knife Information (Jointer)**

Number of Knives .....	2
Knife Type.....	HSS
Knife Length.....	10 <sup>1</sup> / <sub>4</sub> "
Knife Width.....	<sup>11</sup> / <sub>16</sub> "
Knife Thickness.....	<sup>1</sup> / <sub>8</sub> "
Knife Adjustment.....	Jack Screws

**Cutterhead Information**

Cutterhead Type .....	2 HSS Knives
Cutterhead Diameter.....	2 <sup>9</sup> / <sub>32</sub> "
Cutterhead Speed.....	6500 RPM

**Table Information (Jointer)**

Table Length .....	40 <sup>15</sup> / <sub>16</sub> "
Table Width.....	12 <sup>1</sup> / <sub>2</sub> "
Floor To Table Height.....	33 <sup>3</sup> / <sub>4</sub> "

**Table Information (Planer)**

Table Length .....	23 <sup>1</sup> / <sub>8</sub> "
Table Width.....	9 <sup>3</sup> / <sub>4</sub> "
Table Thickness.....	1 <sup>1</sup> / <sub>2</sub> "
Floor To Table Height.....	23"-30"

**Construction**

Body Assembly Construction .....	Sheet Metal
Cutterhead Assembly Construction .....	Steel
Infeed Roller Construction .....	Steel w/Vulcanized Rubber Coating
Outfeed Roller Construction.....	Steel w/Vulcanized Rubber Coating
Jointer Table Construction.....	Cast Iron
Paint.....	Powder Coated

**Other Information**

Dust Port Size .....	4"
Number of Dust Ports .....	1
Measurement Scale (Jointer).....	mm
Measurement Scale (Planer) .....	mm

**Other Specifications:**

Country Of Origin.....	China
Warranty.....	1 Year
Serial Number Location .....	ID Label on Front of the Stand

**Features:**

- Quick release fence
- Flip up outfeed table and change lever simplify jointer-planer conversion
- Vulcanized rubber feed rollers (planer mode)
- Heavy duty cast iron infeed and outfeed tables, easily and accurately adjustable
- Cutterhead guard adjustable for workpiece height
- Dust hood position adjustable for jointer or planer conversion