



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G8692 COMBINATION BENCHTOP/HAND-HELD METAL-CUTTING BANDSAW

Product Dimensions:

Weight..... 31 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 18-1/2 x 13 x 14 in.
Footprint (Length x Width)..... 10 x 18-1/2 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 38 lbs.
Length x Width x Height..... 16 x 24 x 13 in.

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 3A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 5 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... 1-15
Switch Type..... Trigger Switch

Motors:

Main

Horsepower..... 1 HP
Phase..... Single-Phase
Amps..... 12.5A
Type..... Universal
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... N/A

Main Specifications:

Operation Info

Blade Speeds..... 190 , 262 FPM
Std. Blade Length..... 44-7/8 in.
Blade Length Range..... 44-7/8 x 1/2 x 0.025 in.

Cutting Capacities

Cutting Capacity Left of Blade..... 4-3/4 in.
Angle Cuts..... 90 deg.
Vise Jaw Depth..... 4-3/4 in.
Vise Jaw Height..... 3 in.
Max. Capacity Rectangular Height at 90 Deg..... 4-1/2 in.
Max. Capacity Rectangular Width at 90 Deg..... 4-3/4 in.
Max. Capacity Round at 90 Deg..... 4-3/4 in.

Construction

Table.....	Sheet Metal
Upper Wheel.....	Rubber Coated Aluminum
Lower Wheel.....	Rubber Coated Aluminum
Tire.....	Rubber
Body.....	Aluminum & Plastic
Base.....	Sheet Metal
Stand.....	Sheet Metal
Wheel Cover.....	Sheet Metal
Paint Type/Finish.....	Epoxy

Other

Blade Guides Upper.....	Ball Bearing
Blade Guides Lower.....	Ball Bearing

Table Info

Table Size Length.....	7-1/2 in.
Table Size Width.....	5-1/2 in.

Other Specifications:

ISO 9001 Factory	Yes
------------------------	-----

Features:

- Includes Stand with Locking Vise
- Double Insulated